

**DeVilbiss spray guns have *Advanced* again with the introduction of a new conventional spray gun range suitable for all Industrial spray applications.**

The DeVilbiss Advance *HD* (High Demand) spray guns are available in Pressure, Suction and Gravity feed formats and a wide range of conventional technology Air Caps provide exceptional atomisation for coating wood, metal, plastic, ceramic and composite substrates with most types of solvent, waterborne, high solids and 2K materials.

**DeVilbiss outperforms the rest.**

Advance *HD*'s unique high capacity airflow and outstanding atomisation characteristics are combined with a separate "balanced" air valve to provide an unrestricted flow of compressed air through the gun body, this coupled with light, feel right comfort is an unbeatable combination. Advance spray guns are ideal for small operations or high volume spraying, with the added bonus of instantly improved finishing productivity.

Advance *HD* is precision built by DeVilbiss using the best materials and component parts for a guaranteed, reliable, long and durable working life in all industrial markets.



*Advance*  
**HD**  
 by **DEVILBISS**.

## The all purpose mid sized Conventional spray gun range

- Wide range of conventional atomisation air caps provide a superior sprayed finish
- Robust, Lightweight and work friendly design for **High Demand** outputs
- Stainless Steel tips, needles and fluid passageways as standard
- Contoured handle design – Greatly reduces RSi and operator fatigue
- CE marked and fully ATEX approved

## Advance HD by DEVILBISS.

Advance HD's unrivalled spray performance is achieved with the utilisation of the very latest "cutting edge" atomisation technology. Advance has a wide range of high-grade Stainless Steel Fluid Tips and Needles, matched with Conventional Air Caps, manufactured from Plated Hard Brass for a long and durable working life. Select your Advance spray gun preference and nozzle combination's from the charts below to provide the Optimum performance for your individual spray process.

### Example of Advance HD spray gun part numbering:- ADV-P430-14 means...

ADV = Advance gun / P = Pressure / 430 = Conventional Air Cap / 14 = 1.4mm Fluid tip and needle.

Advance HD spray guns kits are packaged as:- Pressure gun only, Suction gun with 1 litre cup and Gravity feed kits inc. 568 ml standard gravity cup.



Suction cup  
pt. no. TGC-545-E-K



Gravity cup  
pt. no. GFC 501



Gravity cup (Blue polyester)  
pt. no. GFC 511 for difficult fluids.



### Optional accessories

1. VSA-512 St/St Fluid Filter Kit (inc. 3 elements)
2. Tungsten Carbide and Hardened Tips/Needles (for use on abrasive materials)
3. Nylon Tipped Needle.

Air Cap Number and Type	Air Consumption	Air Inlet Pressure Bar (psi) recommended	*Typical Fluid Flow ml	*Typical Fan Pattern size mm
No. 430 Conventional	339 l/min (12 scfm)	3.5 bar (50 psi)	200-280	200
No. 443 Conventional	345 l/min (12.3 scfm)	3 bar (45 psi)	200-300	300
No. 470 Conventional	465 l/min (16.4 scfm)	3 bar (45 psi)	500-1800†	420†
No. 497 Conventional	510 l/min (18 scfm)	3.5 bar (50 psi)	200-600	380

All illustrated flow rates and fan sizes may vary according to paint/material viscosity and pressures used.

† = ceramic material

### Tip and Cap Chart


Air Cap No.	Technology	0.85 mm	1.0 mm	1.2 mm	1.3 mm	1.4* mm	1.6 mm	1.8* mm	2.0 mm	2.2* mm	2.8* mm
430	Conventional	P	P	P	P G	P	P G S	P G S	P G S	P S	
443	Conventional	P	P	P	P G	P	P G S	P G S	P G S	P S	
470	Conventional									P	P
497	Conventional	P	P	P	P	P	P	P	P	P	P

P = Pressure G = Gravity S = Suction \* Hardened and tungsten carbide tips and needles are available in these sizes.

### Spray gun inlet thread sizes & type:-

Air Connection 1/4" (m) Universal Thread size, accepts BSP and/or NPS connectors.  
Fluid Connection 3/8" (m) Universal Thread size, accepts BSP and/or NPS connectors.

For further technical information please refer to the Advance HD Service Bulletin



### ITW Industrial Finishing

Ringwood Road, Bournemouth, England BH11 9LH  
Tel: +44 (0)1202 571111  
Fax: +44 (0) 1202 573488  
Email: industrial.mktg@itwfinishing.co.uk

### ITW Oberflächentechnik GmbH

Justus-von-Liebig-Strasse 31,  
63128 Dietzenbach Germany  
Tel: +49 (0) 6074-403-1  
Fax: +49 (0) 6074-403-281  
Email: marketing@itw-finishing.de

### ITW Surfaces et Finitions

163-171 Avenue des Auréats, BP 1453  
26014 Valence cedex FRANCE  
Tel: +33(0)4 75 75 27 00  
Fax: +33(0)4 75 75 27 59  
Email: mkt@itwssf.com